



# P5

## L/C/R/Surround Speaker

### Technical Specifications



- Procella performance for the first time in this size and price class
- Main and surround speaker for small to mid-size rooms up to 20 feet in depth
- 1" compression driver on circular constant directivity waveguide: 80° from 2.5kHz
- 5.25" high-output pro woofer driver
- Identical Voice™ timbre-matched to all Procella models
- Sealed-box design
- Can be oriented horizontally or vertically
- Black or White cabinet finish
- Can be used with or without optional cloth grille (magnetically attached)

**Impedance** 8 Ohms nominal  
Phase angles less than 45 degrees

**Power handling**  
Continuous 75 Watt  
Peak 250 Watt

**Sensitivity**  
1m/1W 91dB

**Maximum SPL**  
free-standing 107dB continuous, 113dB peak  
in wall 113dB continuous, 119dB peak

**Frequency response**  
-3dB points 90Hz and 20kHz

**Dispersion pattern**  
-6dB Constant directivity;  
80° circular from 2.5kHz

**Crossover** Asymmetrical and phase aligned  
2.2kHz, BSC

**Components**  
Midrange 5.25" driver with 26mm voice coil in 5 litre sealed box  
High Frequency 1" compression driver on a circular constant directivity wave guide

**Connectivity** Gold plated large diameter binding posts

**Wall Mount** Keyholes provided for both vertical and horizontal mounting

**Finish** White or Black semi-matte painted finish. MDF construction, removable cloth grille

**Dimensions**  
HxWxD 12" x 7.5" x 6.7" / 304 x 190 x 170 mm

**Shipping Carton**  
HxWxD 15.75" x 11.8" x 10.4" / 400 x 300 x 265 mm

**Net weight** 9.9 Lbs / 4.5Kg

**Shipping weight** 12.1 Lbs / 5.5Kg

**Assembly** Sweden; 100% QC testing