

passive loudspeaker P5V

LCR - Wide - Surround - Height







INTRODUCTION

The P5V delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver. The P5V comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

8 ohms nominal **Impedance**

Phase angles less than

45 degrees

Power Handling

75W Continuous 250W Peak

Frequency Response

- 3 dB 90Hz and 20kHz

Maximum SPL

free standing 107dB continuous 113dB peak in wall 113dB continuous 119dB peak

Dispersion pattern

80° circular from 2.5kHz -6dB

Sensitivity

1m/1W 91dB

Crossover Asymmetrical, phase aligned

2.2kHz, BSC

Constant directivity

Components

Midrange 5.25" driver with 26mm voice coil

in 5 litre sealed box

High Frequency 1" compression driver on a

circulair constant directivity waveguide

Connectivity Gold plated large diameter binding posts

Wall Mount 1Inserts for VESA 100 bracket and

keyholes provided for both vertical

and horizontal mounting

Finish White or Black semi-matte painted finish.

Dimensions 18.5" x 7.5" x 4,5" HxWxD

470 x 190 x 115 mm

Shipping Carton 23.6" x 11.6" x 7.9" HxWxD 600 x 295 x 200 mm

Net weight 11 Lbs / 5 Kg

Shipping weight 13,2 Lbs / 6 Kg

Assembly Sweden; 100% QC testing