

# P15 - SUBWOOFER



## Dual 15 Inch Passive Subwoofer

### INTRODUCTION

In an astonishingly compact enclosure (just 8.75" / 222mm deep), the P15 subwoofer brings the authority and impact of the mighty P18 to medium and small rooms where nothing less than the best bass quality will do. Its dual 15-inch long-throw Italian pro audio subwoofer drivers have 3" voice coils and are mounted in a sealed-box heavily-braced enclosure. The P15 is driven by external amplification with DSP. The P15 blends lightning-quick transient response with massive impact. Capable of 125dB output and able to reproduced bass frequencies in-room flat to 22Hz and below, the P15 is the ideal low-frequency source for mid-sized domestic and professional environments.

### TECHNICAL SPECIFICATIONS

**Impedance** Each driver is 8 ohms nominal

**Frequency Response**  
-3dB 22Hz

**Maximum SPL @ 50Hz**  
Continuous 119dB  
Peak 125dB

**Components** Dual long-throw pro audio drivers with cast aluminium. Chassis and ferrite magnets in 75l sealed box.

**Power Handling**  
Continuous 2 x 800W  
Peak 2 x 1.600W

**Sensitivity**  
1m/1W 97dB

**Connectivity** Dual gold plated binding posts.  
One input per driver

**Construction** Heavily internally braced MDF,  
Black painted finish

**Dimensions** 22.4" x 36.6" x 8.75"  
HxWxD 570 x 930 x 222 mm

**Shipping Carton** 27.2" x 42.5" x 15"  
HxWxD 690 x 1080 x 380 mm

**Net Weigth** 92 Lbs / 41,7 Kg

**Shipping Weight** 105 Lbs / 47,7 Kg (plus pallet)

**Included** Damper feet, parallel input cables

**Assembly** Belgium; 100% QC testing

**Amplification** External amplifier is required

**Two channels of external amplification are required.**  
**Procella amplifiers are sold and packaged seperately.**  
**See Tech Sheets for specifications.**

