

P21si - SUBWOOFER



Single 21 Inch Passive Subwoofer

INTRODUCTION

Today's highest-performance systems demand serious low-frequency authority, and the P21Si delivers. Building on Procella's sealed-box heritage, this single 21" subwoofer combines immense output with tight, accurate control, making it the perfect solution where ultra-deep extension meets space efficiency. Using the same driver technology found in our flagship V21, the P21Si's 110-litre enclosure houses a 21" professional-grade driver with a 4.5" voice coil and neodymium magnet, achieving -3dB at 21Hz with remarkable transient precision. Capable of 124.7 dB continuous and 127.4 dB peak SPL @ 50Hz, the P21Si delivers cinematic bass in a compact form. Paired with the Procella DA08-DSP amplifier, it becomes a full-frequency powerhouse.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal	Dimensions	805x700x290mm (grille 300mm) HxWxD 31.7x27.6x11.4 inch (grille 11.8)
Frequency Response -3dB	21Hz	Shipping Carton HxWxD	803x908x375mm
Maximum SPL @ 50Hz Continuous Peak	124.7dB 127.4dB	Net Weight	48 Kg
Components	Professional 21" driver 4.5" voice coil Neodymium magnet 110 litre sealed enclosure	Shipping Weight	52 Kg
Power Handling Continuous Peak	1800W 3600 W	Assembly	Belgium; 100% QC testing
Sensitivity 1m/1W	97dB	Amplification	1 channel, Procella DA08-DSP * Build-in preset for P21Si
Connectivity	Gold plated binding posts	Procella Amplifiers are sold and packaged seperately	
Construction	Internal heavily braced MDF Semi-matte textured black lacquer		

