P5 - LOUDSPEAKER



PERFECTED

Main, Surround & Height Channels

INTRODUCTION

The P5 delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver.

The P5 comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

Impedance 8 ohms nominal Phase angles less than

45 degrees

Power Handling

Continuous 75W Peak 250W

Frequency Response

-3dB 90Hz and 20Hz

Maximum SPL

Freestanding Peak 107dB continuous 113dB In wall Peak 113dB continuous 119dB

Dispersion Pattern

-6dB Constant directivity; 80° circular from 2.5kHz

Sensitivity
Im/IW 91dB

1111/11/1

Crossover Asymmetrical, phase aligned

2.2kHz, BSC

Finish White or Black semi-matte painted

Components

Midrange 5.25" driver with 26mm voice coil in

5 litre sealed box

High Frequency 1' compression driver on a circular

constant directivity waveguide

Connectivity Gold plated large diameter

binding posts

Wall Mount 1 Inserts for VESA 100 bracket and

keyholes provided for both vertical

and horizontal mounting

Dimensions

HxWxD 12" x 7.5" x 6.7"

303 x 190 x 170 mm

Shipping Carton

HxWxD 15.35" x 11.4" x 10.25" 390 x 290 x 260 mm

Net Weigth 10.6 Lbs / 4.8 Kg

Shipping Weight 12.3Lbs / 5 Kg

Assembly Belgium; 100% QC testing





